



GENESIS METALS
JAMES METALS
RIVERSIDE PROCESSING

EQUIPMENT & CAPABILITIES

Slitter

30 gauge min. to ¼" max. (non-high strength steel)
62" max. coil width
50,000 lb. max. coil capacity
74" max outside dimensions (O.D.) on entry and exit
Min. slit width of .625 on 12 gauge and lighter; 1" min. slip width on 11 gauge and heavier
Recoil all material to 20" inside dimensions (I.D.)

96" Heavy Gauge Leveler

14 gauge min. to ½" max.
96" max. coil width
50,000 lb. max. coil capacity
Capable of leveling floor plate
Length range 60" to 500"
Max. O.D. 74"

66" Light Gauge Leveler

30 gauge min. to 11 gauge max.
62" max. coil width
40,000 lb. max. coil capacity
Length range 30" to 240"
Max. O.D. 65"

Shears / Press

3/16' X 10'; (2) ¼" X 12'; 3/8" x 8'; (2) ¼' x 10'; 10ga x 6' ; ½" x 6'; 12ga x 4'; 3/16" x 12'; 10ga x 4'; ¼" x 14';
¾" x 10'; 12ga x 4'; 3/16" x 20'; 150 ton Press; (2) 300 ton Press

Burning Table

Bug-O-Matic (Track Burner)
Single Head Oxy-Fuel Station
Cuts Mild Steel / rectangles & squares
Up to 120" wide and 480" long
1/8" min. / 4" max. thickness
Beveling capabilities – Inquire

72" Heavy Gauge Leveler

11 gauge min. to ¼" max.
72" max. coil width
50,000 lb. max. coil capacity
Length range 48" to 177"
Max. O.D. 69"

60" Light Gauge Leveler

26 gauge min. to 14 gauge max.
60" max. coil width
40,000 lb. max. coil capacity
Length range 30" to 177"
Max. O.D. 69"

Koike CNC Table
Four Head Oxy-Fuel Station
Cuts Mild Steel / various shapes
Up to 96" wide and 240" long
½" min. / 2.5" max. thickness
Beveling capabilities – Inquire

Overhead Cranes

(2) 30 ton; (1)25 ton; (5) 15 ton; (2) 10 ton; (2) 5 ton; (2)3 ton; (1) 55k Combilift RTG

Forklifts

55,000# Kalmar; (2) 55,000# Kone; 36,000# Kalmar; 33,000# Mitsubishi; (15) 12,000# Yale/Chase; (2) 15,500# Yale/Chase;
30k Combilift Side Loader

Trucks

(10) Kenworth T800 Tractors; (1) Kenworth T370 Tractor

08/2017